

# Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Revision date: 17/12/2010

Version EN 1

Page: 1/5

## 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### PRODUCT IDENTIFIER

Quartz

### REACH REGISTR. N°:

Exempted in accordance with Annex V.7

### TRADE NAMES:

## Silica sands and Super-fine silica sands

### RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Main applications (non exhaustive list): paint, ceramics, glass fibre, adhesives, plastics, rubber sealants, special concrete, manufacture of silicon, ferrosilicon and ironoxide pellets. Additive in production of cement and concrete. Fluxing material.

### DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

### COMPANY/UNDERTAKING IDENTIFICATION

Strobel Quarzsand GmbH  
Freihung sand 3  
D 92271 Freihung  
Phone N°: +49 (0) 9646-9201-0  
Fax N°: +49 (0) 9464-1257

### E-MAIL OF RESPONSIBLE PERSON FOR SDS:

[quenter.forster@strobel-quarzsand.de](mailto:quenter.forster@strobel-quarzsand.de)

### EMERGENCY TELEPHONE NUMBER

+49 (0)961-46163/+49 (0) 9646-920115

### AVAILABLE OUTSIDE OFFICE HOURS?

Yes

## 2. SECTION 2: HAZARDS IDENTIFICATION

### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

This product does not meet the criteria for classification as hazardous as defined in the Regulation EC 1272/2008 and in Directive 67/548/EEC.

Depending on the type of handling and use (e.g. grinding, drying), airborne respirable crystalline silica may be generated. Prolonged and/or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness. Occupational exposure to respirable crystalline silica dust should be monitored and controlled.

This product should be handled with care to avoid dust generation.

### REGULATION EC 1272/2008:

No classification

### CLASSIFICATION EU (67/548/EEC):

No classification

This product contains less than 1% quartz (respirable)

### LABEL ELEMENTS

none

### OTHER HAZARDS

This product is an inorganic substance and does not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH.

## 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### MAIN CONSTITUENT

Quartz

### AMOUNT:

SiO<sub>2</sub> > 98%

### E.I.N.E.C.S.-N°

238-878-4

# Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Revision date: 17/12/2010

Version EN 1

Page:2/5

## IMPURITIES

This product contains less than 1% of quartz (respirable), which is classified as STOT RE1.

## **4. SECTION 4: FIRST AID MEASURES**

### DESCRIPTION OF FIRST AID MEASURES

#### EYE CONTACT:

Rinse with copious quantities of water and seek medical attention if irritation persists.

#### INHALATION:

Movement of the exposed individual from the area to fresh air is recommended.

#### INGESTION:

No first-aid measure required.

#### SKIN CONTACT:

No special first aid measures necessary.

### MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

No acute and delayed symptoms and effects are observed.

### INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No special measure.

## **5. SECTION 5: FIREFIGHTING MEASURES**

### EXTINGUISHING MEDIA

No specific extinguishing media is needed.

### SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Non combustible. No hazardous thermal decomposition.

### ADVICE FOR FIREFIGHTERS

No specific fire-fighting protection is required.

## **6. SECTION 6: ACCIDENTAL RELEASE MEASURES**

### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Avoid airborne dust generation, wear personal protective equipment in compliance with national legislation.

### ENVIRONMENTAL PRECAUTIONS:

No special requirements.

### METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Avoid dry sweeping and use water spraying or vacuum cleaning systems to prevent airborne dust generation. Wear personal protective equipment in compliance with national legislation.

### REFERENCE TO OTHER SECTIONS

See sections 8 and 13.

## **7. SECTION 7: HANDLING AND STORAGE**

### PRECAUTIONS FOR SAFE HANDLING

Avoid airborne dust generation. Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment. Handle packaged products carefully to prevent accidental bursting. If you require advice on safe handling techniques, please contact your supplier or check the Good Practice Guide referred to in section 16.

Do not to eat, drink and smoke in work areas; wash hands after use; remove contaminated clothing and protective equipment before entering eating areas.

### CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

### TECHNICAL MEASURES/PRECAUTIONS

Minimise airborne dust generation and prevent wind dispersal during loading and unloading. Keep containers closed and store packaged products so as to prevent accidental bursting.

### SPECIFIC END USE(S)

If you require advice on specific uses, please contact your supplier or check the Good Practice Guide referred to in section 16.

## **8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### CONTROL PARAMETERS

Follow workplace regulatory exposure limits for all types of airborne dust (e.g. total dust, respirable dust, respirable crystalline silica dust).

The OEL (Occupational Exposure Limit) for respirable crystalline silica dust is 0,1 mg/m<sup>3</sup> in the United Kingdom, measured as an 8 hour TWA (Time Weighted Average). For the equivalent limits in other countries, please consult a competent occupational hygienist or the local regulatory authority.

# Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Revision date: 17/12/2010

Version EN 1

Page:3/5

## EXPOSURE CONTROLS:

### APPROPRIATE ENGINEERING CONTROLS

Minimise airborne dust generation. Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Apply organisational measures, e.g. by isolating personnel from dusty areas. Remove and wash soiled clothing.

### INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

#### EYE/FACE PROTECTION

Wear safety glasses with side-shields in circumstances where there is a risk of penetrative eye injuries.

#### SKIN PROTECTION

No specific requirement. For hands, see below. Appropriate protection (e.g. protective clothing, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin.

#### HAND PROTECTION:

Appropriate protection (e.g. gloves, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin. Wash hands at the end of each work session.

#### RESPIRATORY PROTECTION:

In case of prolonged exposure to airborne dust concentrations, wear a respiratory protective equipment that complies with the requirements of European or national legislation.

#### ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid wind dispersal.

## **9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

#### APPEARANCE:

solid

#### GRAIN SHAPE:

angular/rounded

#### COLOR

grayish/beige

#### ODOUR:

Odourless

#### ODOUR THRESHOLD

Not relevant

#### PH-Value

pH (400 g/l water at 20°C)

6.5 - 7

#### MELTING POINT/FREEZING POINT

>1550°C

#### RELATIVE DENSITY:

1,32 – 1,37 g/cm<sup>3</sup>

#### SOLUBILITY(IES)

#### SOLUBILITY IN WATER

Negligible

#### SOLUBILITY IN HYDROFLUORIC ACID

Yes

#### OTHER INFORMATION

no other information

## **10. SECTION 10: STABILITY AND REACTIVITY**

### REACTIVITY

Inert, not reactive.

### CHEMICAL STABILITY

Chemically stable

### POSSIBILITY OF HAZARDOUS REACTIONS

No hazardous reactions.

### CONDITIONS TO AVOID:

Not relevant

### INCOMPATIBLE MATERIALS

No particular incompatibility.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Not relevant

## **11. SECTION 11: TOXICOLOGICAL INFORMATION**

### INFORMATION ON TOXICOLOGICAL EFFECTS

#### ACUTE TOXICITY

Based on available data, the classification criteria are not met.

# Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Revision date: 17/12/2010

Version EN 1

Page:4/5

## SKIN CORROSION/IRRITATION

Based on available data, the classification criteria are not met.

## SERIOUS EYE DAMAGE/IRRITATION

Based on available data, the classification criteria are not met.

## RESPIRATORY OR SKIN SENSITISATION

Based on available data, the classification criteria are not met.

## GERM CELL MUTAGENICITY

Based on available data, the classification criteria are not met.

## CARCINOGENICITY

Based on available data, the classification criteria are not met.

## REPRODUCTIVE TOXICITY

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## ASPIRATION HAZARD

Based on available data, the classification criteria are not met.

## **12. SECTION 12: ECOLOGICAL INFORMATION**

### TOXICITY

Not relevant

### PERSISTENCE AND DEGRADABILITY

Not relevant

### BIOACCUMULATIVE POTENTIAL

Not relevant

### MOBILITY IN SOIL

Negligible

### RESULTS OF PBT AND VPVB ASSESSMENT

Not relevant

### OTHER ADVERSE EFFECTS

no specific injurious effects are known

## **13. SECTION 13: DISPOSAL CONSIDERATIONS**

### WASTE TREATMENT METHODS

### WASTE FROM RESIDUES/UNUSED PRODUCTS

Where possible, recycling is preferable to disposal. Can be disposed of in compliance with local regulations.

### PACKAGING

Dust formation from residues in packaging should be avoided and suitable worker protection assured.

Store used packaging in enclosed receptacles.

Recycling and disposal of packaging should be carried out in compliance with local regulations.

The re-use of packaging is not recommended. Recycling and disposal of packaging should be carried out by an authorised waste management company.

## **14. SECTION 14: TRANSPORT INFORMATION**

### UN NUMBER

Not relevant

### UN PROPER SHIPPING NAME

Not relevant

### TRANSPORT HAZARD CLASS(ES)

ADR: Not classified

IMDG: Not classified

ICAO/IATA: Not classified

RID: Not classified

### PACKING GROUP

Not relevant

### ENVIRONMENTAL HAZARDS

Not relevant

### SPECIAL PRECAUTIONS FOR USER

No special precautions.

### TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not relevant

# Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Revision date: 17/12/2010

Version EN 1

Page:5/5

## 15. SECTION 15: REGULATORY INFORMATION

### SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE CHEMICAL SAFETY ASSESSMENT

Exempted from REACH Registration in accordance with Annex V.7.

## 16. SECTION 16: OTHER INFORMATION

### THIRD PARTY MATERIALS

Insofar as materials not manufactured or supplied by Strobel Quarzsand GmbH are used in conjunction with, or instead of Strobel Quarzsand GmbH materials, it is the responsibility of the customer himself to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of Strobel Quarzsand GmbH's products in conjunction with materials from another supplier.

### LIABILITY:

Such information is to the best of Strobel Quarzsand GmbH's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

### TRAINING

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

### SOCIAL DIALOGUE ON RESPIRABLE CRYSTALLINE SILICA

A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from <http://www.nepsi.eu> and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers.

Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003).

So there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see section 16 below).

(\*) = Due to new legal changes the material safety data sheet has completely been revised.